



Polycom® VSX™ 3000



Benefits

Completely Integrated – All-in-one video conferencing system includes camera, display, speakers, cables and microphone

Versatile Display – Built-in 17" LCD flat screen with added ability to act as a high resolution PC desktop display

Superior Audio – Polycom Siren™ 14 with integrated speakers delivers 14 kHz of wideband sound while the Siren 14 Stereo delivers that same incredible audio in rich stereo

Outstanding Video – Premium quality video at any bandwidth with standards based H.264

Easiest to Use – User-friendly and customizable graphical interface makes video conferencing a breeze and provides maximum user flexibility

Portable – Sleek, compact design delivers high-quality, face-to-face video communication within space constrained environments. Simply plug into any IP or ISDN network

Maximum Calling Capacity – Internal multipoint (optional) connects up to four video sites (IP, ISDN or mixed) directly from the Polycom VSX 3000 in a continuous presence or voice activated mode – see all callers at once or one at a time. ISDN voice callers can be added within the internal multipoint function

Enhanced Features – Integrated AES encryption for secure calls

The Polycom Solution – Everything you need to deploy and manage a complete video conferencing network with Polycom Global Management System™, Polycom PathNavigator™, Polycom Conference Suite and the Polycom MGC™

The world's most advanced, fully integrated video conferencing system for executive office and remote offices.

The Polycom VSX 3000 is a stylish and compact video conferencing system that provides excellent video and audio quality. Featuring an integrated LCD screen, the Polycom VSX 3000 is the perfect video conferencing solution for executive suites and remote offices. As a fully integrated video conferencing system, the Polycom VSX 3000 is easier to use in a shared environment, delivering ease of use with powerful video and audio performance. The Polycom VSX 3000 also can act as a PC display when not in a video call - saving valuable desk space.

For executives, the Polycom VSX 3000 allows video calls around the world directly from their offices, eliminating the need to find an available conference room. The Polycom VSX 3000 frees up large conference rooms by moving calls requiring only a few individuals to a smaller meeting space. And for remote locations, the Polycom VSX 3000 helps off-site professionals such as regional sales representatives and consultants to stay in touch with corporate headquarters for training, meetings or face-to-face contact without the investment or space required for a large video conferencing system, or the continuous cost of plane tickets.

The Polycom VSX 3000 offers intuitive navigation with an enhanced graphical user interface, including a hand held remote control. TV-like video with H.264 video technology, Pro-Motion™ video, and near CD-quality audio with Polycom Siren 14 and the optional Siren 14 Stereo enables the delivery of high-quality video conferencing over IP and ISDN networks. And as an integrated component of the Polycom conferencing solution, the Polycom VSX 3000 works well for one-to-one or one-to-many communications.

The integrated video conferencing system of choice period. The power of Polycom conferencing and collaboration solutions.

With integrated video, voice, data, and Web capabilities, only Polycom solutions let you connect, conference, and collaborate anytime, anywhere and any way you want. It's our commitment to making distance communications as natural and interactive as being there. Work faster, smarter, and more efficiently with Polycom VSX 3000 and Polycom conferencing and collaboration solutions.



Connect. Any Way You Want.

Polycom VSX 3000 Specifications

ITU H.323 and H.320 compliant

Bandwidth

- Maximum Data Rate IP: Up to 2 Mbps
- Maximum Data Rate ISDN: Up to 512 kbps

Video Standards

- H.261, Annex D
- H.263+ Annexes: F, I, J, L, N, T
- H.263++ Annexes: W
- H.264
- ITU 60-fps full screen – Pro-Motion

Frame Rates (Point-to-Point)

- Intelligently selects frame rate for best performance video
- 30 fps at 56 kbps up to 2 Mbps
- Up to 60 fields per second - up to 2Mbps

Video Inputs

- Integrated main camera
- 1 x Composite; RCA/Photo (Document camera, VCR or second camera)

Video Formats

- NTSC/PAL

Integrated Main Camera

- 60° field of view
- Tilt Range: +/- 20° (Up/Down)
- Pan Range: +/- 20° (Left/Right)
- Total Field of View: 100°
- Automatic white balance

People Video Resolution

- Pro-Motion interlaced video (60/50 fields full-screen video for NTSC/PAL) – VCR/Doc cam only
- SIF (352 x 240)
- CIF (352 x 288)

Content Video Resolution

- Up to 4CIF

Audio Standards & Protocols

- Polycom Siren 14 Stereo Ready
- 14 kHz bandwidth with Siren 14 on IP, ISDN, and IP/ISDN mixed calls
- 7 kHz bandwidth with G.722, G.722.1
- 3.4 kHz bandwidth with G.711, G.728, G.729A

Audio Features

- ISDN voice calls
- Full-duplex digital audio
- Instant Adaptation Echo Cancellation
- Automatic Gain Control (AGC) - Voice activated
- Automatic Noise Suppression (ANS)
- Built-in tonal speaker test microphones
- Ability to talk over VCR audio

Audio Inputs

- Built-in dual microphones with wide coverage area
- 2X RCA stereo line level for VCR

Audio Outputs

- Built-in dual speakers, with separate audio volume control on video conferencing and PC monitor functionalities
- Headphone in front panel (3.5 mm stereo mini jack)
- Auxiliary line-level in back panel (3.5 mm stereo mini jack)

Other ITU-Supported Standards

- H.221 communications
- H.224/H.281 far-end camera control
- Annex Q standard for FECC in H.323 calls
- H.225, H.245, H.239(receive), H.241
- H.231 in multipoint calls
- H.243 MCU password
- H.233, H.234, H.235V3 AES encryption standards
- Bonding, Mode 1

Network Interfaces Supported

- IP (LAN, DSL, cable modem)
- Single 10/100 Ethernet port (10 Mbps/100Mbps/Auto)
- Integrated Quad BRI (Basic Rate Interface)
- Optional wireless LAN support via Ethernet port
 - Compliant with IEEE 802.11b or 802.11g, up to 54 Mbps
 - Support for 64-bit to 128-bit encryption (WEP)
 - Infrastructure or ad-hoc mode

Network Features

- Integration with Cisco Systems Call Manager V4.0
- Automatic IP/ISDN calling
- Down speeding over IP and ISDN
- IP address conflict warning
- Fast Connect IP for quick video connections
- Maximum call length digital timer
- Auto SPID detection and line number configuration
- MGC™ Click & View™ for individual screen layouts
- Polycom OneDial™ intelligent call management attempts call on preferred network (IP or ISDN) and automatically rolls over to secondary network if needed
- PathNavigator support for easy call placement and network cost optimization
- TCP/IP, DNS, WINS, DHCP, ARP, HTTP, FTP, Telnet
- Software Upgradeable Inverse Multiplexer (IMUX)
- Basic SIP * (Session Initiation Protocol) Implementation

Internal Multipoint (Optional)

- Mixed protocol dialing connects a total of four endpoints through the internal MCU
- Dial-in/Dial-out Calling
- Password protection for incoming calls
- Supports IP telephones
- Automatic IP/ISDN down speeding
- Supports People+Content™ from any endpoint (not just the host site)
- Voice Activated Switching (VAS)
- Continuous Presence- sell all locations
- Automatic Presentation- switch between presenter and continuous presence mode
- Audio add-in over ISDN
- MP key installation while in a call

Conference on Demand

- Initiates unscheduled MGC calls from the endpoint
- Utilizes the Polycom Office™ (Polycom PathNavigator and MGC)
- Auto selects either the internal or external bridge
- Dials all participants simultaneously

Security

- Account validation number entry
- SNMP trap notification of all failed login attempts from HTTP, FTP or Telnet
- Secure password authentication
- Unique factory default passwords
- Administrator password
- Dial-in meeting password
- Encrypted password for VSX Web access
- Ability to disable mixed protocol multipoint calls
- Auto-Answer (On/Off)
- Allow access to user settings (On/Off)

Embedded Encryption

- Advanced Encryption Standard (AES)
- FIPS validated by National Institute of Standards & Technology (NIST) certified agency
- 128-bit key length
- AES software encryption on ISDN, IP (up to 2 Mbps)
- Standards-based H.235V3 (IP)
- Standards-based H.233/H.234 (ISDN/Serial)
- Automatic key generation and exchange
- Supported in People+Content™
- Supported in Point-to-Point IP & ISDN & mixed multipoint calls

User Interface

- User-friendly graphical interface
- Customizable home screen and color themes
- Kiosk mode with scrolling marquee
- User-selectable camera icons and ring tones
- Speed Dial List on home page
- Persistent Preview (Far-site PIP) on all screens
- Picture In Picture (PIP) (On/Off, Moveable)
- Dual Monitor Emulation
- Numerical menu navigation (Similar to mobile phone)
- Date, Time Server accessibility
- Calendar and Conference scheduling
- Alert Signal on home page
- Do Not Disturb (On/Off)
- VSX Web for remote monitoring
- Customizable home screen and color themes
- Kiosk mode with scrolling marquee
- User-selectable camera icons and ring tones
- Speed Dial List on home page
- Persistent Preview (Far-site PIP) on all screens
- Picture In Picture (PIP) (On/Off, Moveable)
- Dual Monitor Emulation
- Numerical menu navigation (Similar to mobile phone)
- Date, Time Server accessibility
- Calendar and Conference scheduling
- Alert Signal on home page
- Do Not Disturb (On/Off)
- Web for remote monitoring (enabled/disabled from endpoint)

Directory Services

- 4,000 number global directory
- 1,000+ number local directory
- Limitless multipoint entries
- Live address book with Polycom Global Directory Services automatically and quickly updates directory with address changes or new endpoints
- Live address book with Polycom Global Directory Services automatically and quickly removes endpoints from directory if they are turned off
- Polycom Global Directory Services integrates with Active Directory/LDAP
- Directory Server backup in the event Polycom Global Directory is not accessible
- Automatic ISDN localization of calls

System Management

- SNMP for enterprise management
- Diagnostics and software upgrades via PC, LAN
- Integrated VSX Web for remote management
- Out-of-box setup from VSX Web
- Place a call from VSX Web
- Language independence between set-top interface and VSX Web
- System configuration from VSX Web
- Recent Calls Log – Records last 99 incoming and outgoing calls
- Call Detail Record (CDR) – Reports all calls made from the system along with call statistics
- CDR Feature On/Off
- Downloadable CDR data for processing requires no external management system
- Account number validation at call initiation integrated with Polycom Global Management System™ for billing purposes
- Administrator-configurable dialing speeds
- Complete support for The Polycom Office including:
 - Polycom Global Management System
 - Polycom OneDial
 - Polycom PathNavigator
 - Polycom Conference Suite
 - Polycom MGC

Quality of Service and Experience – iPriority™

- Video Error Concealment
- Audio Error Concealment
- Universal Plug and Play (UPnP)
- IP Precedence (ToS)
- DiffServ (DSCP) (COS)
- Dynamic Bandwidth Allocation
- Proactive Network Monitoring
- Packet and jitter control

- Network Address Translation (NAT) support
- Automatic NAT discovery
- Configurable video/audio/FECC service value
- Asymmetric speed control
- Alternate Gatekeeper
- TCP/UDP fixed-port firewall support
- Lip synchronization
- Echo cancellation
- Echo suppression
- Auto gatekeeper discovery
- Automatic gateway dialing profiles
- Specify outbound call routing for gateway/ISDN

Collaboration Solutions

- Closed captioning support
- Web Streaming in and out of a call, RTP based, suitable with QuickTime players

Language Support (11 languages)

- Chinese (Simplified), Chinese (Traditional), English, French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Spanish and Russian
 - Documentation translations in all languages
 - User interface translations in all languages
 - Keypad audio dialing confirmation in all languages
 - VSX Web translations in all languages
 - Remote controls labeled in all languages

PC Monitor functionality

- Alternative use of display as PC monitor
- VGA input (up to SXGA, 1280x1024)
- VGA output as pass-through of VGA input
- Built-in stereo speakers for PC audio, with separate audio volume control from video conferencing functionality
- Video call audible indication when incoming call during PC monitor use

Electrical

- Auto sensing power supply
- Operating voltage/power 90-260 VAC, 47-63 Hz

Environmental Specifications

- Operating Temperature: 0-40° C
- Operating Humidity: 15-80%
- Non-Operating Temperature: -40-70° C
- Non-Operating Humidity (Non-condensing): 10-90%

Physical Characteristics

- Dimensions (W/H/D): 17.1"/17.5"/4.4"
- 434mm/443mm/112mm
- Weight: 19.2lbs/8.7kg

Warranty

- One-year return to factory parts and labor
- One-year software updates and upgrades

* SIP video extensions are in the process of standard ratification

©2004 Polycom, Inc. All rights reserved.

Polycom and the Polycom logo design are registered trademarks and MGC, Click & View, Polycom PathNavigator, Polycom OneDial, Polycom Office, Global Management System, People+Content, Siren and iPriority are trademarks of Polycom, Inc.

All other trademarks are the property of their respective owners. Information in this document is subject to change without notice.



Polycom Headquarters:

4750 Willow Road, Pleasanton, CA 94588 (T) 1.800.POLYCOM (765.9266) for North America only.
For North America, Latin America and Caribbean (T) +1.925.924.6000, (F) +1.925.924.6100

Polycom EMEA:

270 Bath Road, Slough, Berkshire SL1 4DX, (T) +44 (0)1753 723000, (F) +44 (0)1753 723010

Polycom Asia Pacific:

Polycom Hong Kong Ltd., Rm 1101 MassMutual Tower, 38 Gloucester Road, Wanchai, Hong Kong, (T) +852.2861.3113, (F) +852.2866.8028

Part No. 3726-17017-001 Rev. 6/04